AWTA PRODUCT TESTING

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client: Pipers International Pty Ltd

38 Jesica Road

Campbellfield VIC 3061

Test Number : 19-001650

Issue Date : 2/07/2019

2/07/2019

Print Date

Sample Description Clients Ref : "EIR Matte"

Laminate Flooring Planks
Colour: Timber Look
End Use: Flooring

Nominal Composition: MDF and Decor Layer

Nominal Mass per Unit Area/Density: Approx 11.0kg/m2

Nominal Thickness: 12.3mm

AS/ISO 9239.1-2003 Reaction to Fire Tests for Floorings. Determination of the Burning Behaviour using a

Radiant Heat Source

Date of Sample Arrival 27/03/2019
Date Tested 01/07/2019

CHF Value 2 1 3 Mean Length 7 1 kW/m² Width 66 6.9 7 1 69 kW/m² HF-30 Value 1 2 3 Mean Length 7.5 kW/m² Width 7.3 7.3 7.7 kW/m² Smoke Value 2 1 3 Mean Length 6 %.min Width 14 24 18 19 %.min

Blistering

171094 35063 Page 1 of 2

 Australian Wool testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing - Chemical Testing - Mechanical Testing

985

: Accreditation No. : Accreditation No.

: Accreditation No

983



Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA

Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results

relate only to the sample or samples tested. This document shall not be reproduced except in full and shall

APPROVED SIGNATORY

AICHAEL A. JACKSON B.Sc.(Hons)

AWTA Product Testing

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client: Pipers International Pty Ltd

38 Jesica Road

Campbellfield VIC 3061

Test Number :

19-001650

Issue Date

2/07/2019

Print Date

2/07/2019

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BSEN 13238:2010 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Results in accordance with section 8.4 have not been included in the report. They are available upon request.

Each specimen was clamped to a substrate of 6mm thick fibre reinforced cement board prior to testing.

171094

Australian Wool testing Authority Ltd

Copyright - All Rights Reserved

35063

Page 2 of 2



Accredited for compliance with ISO/IEC 17025 - Testing - Chemical Testing - Mechanical Testing

: Accreditation No.

983

Samples and their identifying descriptions have been provided by the client unless otherwise stated.

Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test

relate only to the sample or samples tested. This document shall not be reproduced except in full and

A. JACKSON B.Sc.(Hons)

0204/11/06

APPROVED SIGNATORY