

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client : Pipers Interr 38 Jesica Ro Campbellfie			Test Num Issue Da Print Dat	te :	19-00165 2/07/2019 2/07/2019	9
Sample Description	Clients Ref : "High Gl Laminate Flooring Planks End Use : Flooring Nominal Composition : Nominal Thickness :					
/ISO 9239.1-2003	Reaction to Fire Tests fo Radiant Heat Source	or Floorings. Determinati	on of the Burning	j Behavi	our using a	
	Date of Sample Arrival 27/03/2019					
	Date Tested 02/07/2019					
	CHF Value	1	2	3	Mean	
	Length	7.5	-	-	-	kW/m²
	Width	7.1	7.8	7.3	7.4	kW/m²
	HF-30 Value	1	2	3	Mean	
	Length	7.8	-	-	-	kW/m²
	Width	7.5	8.0	-	-	kW/m²
	Smoke Value	1	2	3	Mean	
	Length	25	-	-	-	%.min
	Width	19	8	40	22	%.min
	Blistering				Yes	

171088

35064





Accredited for compliance with ISO/IEC 17025 - Testing - Chemical Testing - Mechanical Testing - Performance & Approvals Testing

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

: Accreditation No. : Accreditation No. : Accreditation No.

983 985 1356

Page 1 of 2





JADM

APPROVED SIGNATORY

(C)



Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client : Pipers International Pty Ltd 38 Jesica Road Campbellfield VIC 3061

Test Number	:	19-001651
Issue Date	:	2/07/2019
Print Date	:	2/07/2019

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BSEN 13238:2010 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Results in accordance with section 8.4 have not been included in the report. They are available upon request.

Each specimen was clamped to a substrate of 6mm thick fibre reinforced cement board prior to testing.

171088

Australian Wool testing Authority Ltd Copyright - All Rights Reserved

35064



the Managing Director of AWTA Ltd.

Accredited for compliance with ISO/IEC 17025 - Testing - Chemical Testing - Mechanical Testing - Performance & Approvals Testing

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by

: Accreditation No. : Accreditation No. : Accreditation No.

983 985

1356

AWTĂ

Page 2 of 2





C

SADY